Gerlach 2.0 RDGH-H2/H3/H4






STANDARD FEATURES


- working temperature: from 0°C to 2°C
- refrigerant: R744
- natural defrosting
- 2 x NTC temperature probe
- siphoned condensate drains
- exposition: zinc-plated steel, powder coated in white (RAL 9003)
- 4 rows of suspended shelves, on shelves and on air inlet price holders 39 mm
- lighting: top, LEDit, color NW-4
- color of the base black (RAL 9005
- grey PVC bumper on the front of the unit


OPTIONS

- electronic expansion valve
- sidewall

DVO – door I double, straight (High Vision) I hinged







AVAILABLE MODULES

1250 1875 2150 2500 3750

Gerlach 2.0 RDGH-H2/H3/H4






STANDARD FEATURES


- working temperature: from 0°C to 2°C
- refrigerant: R744
- natural defrosting
- 2 x NTC temperature probe
- siphoned condensate drains
- exposition: zinc-plated steel, powder coated in white (RAL 9003)
- 4 rows of suspended shelves, on shelves and on air inlet price holders 39 mm
- lighting: top, LEDit, color NW-4
- color of the base black (RAL 9005)
- grey PVC bumper on the front of the uni
- mechanical night blind


OPTIONS

- electronic expansion valve
- sidewall:

DVO – door I double, straight (High Vision) I hinged







A ↑ G

2500

E A † G 2500

AVAILABLE MODULES

1250 1875 2150 2500 3750